


# 2015 300-208 Exam Questions PDF Free Download From Braindump2go (111-120)

**CISCO NEW UPDATED: New Updated 300-208 Exam Questions from Braindump2go 300-208 PDF Dumps and 300-208 VCE Dumps! Welcome to Download the Newest Braindump2go 300-208 VCE&PDF Dumps:**

<http://www.braindump2go.com/300-208.html> (89 Q&As) 2015 Latest 300-208 Real exam questions to master and practice upon! Braindump2go Offers the New Updated Cisco 300-208 194 Exam Questions in PDF & VCE files that can also be downloaded on every mobile device for preparation! Vendor: CiscoExam Code: 300-208Exam Name: Implementing Cisco Secure Access Solutions300-208 sisas,300-208 sisas pdf,300-208 sisas book,300-208 sisas training,300-208 sisas implementing cisco secure access solutions,300-208 dumps,300-208 pdf,300-208 Book

**Implementing Cisco Secure Access Solutions: 300-208**



**Product Description Exam Number/Code: 300-208**

**Exam Number/Code: 300-208**

"Implementing Cisco Secure Access Solutions", also known as 300-208 exam, is a Cisco Certification. With the complete collection of questions and answers, Braindump2go has assembled to take you through 194 Q&As to your 300-208 Exam preparation. In the 300-208 exam resources, you will cover every field and category in Cisco CCNP Security helping to ready you for your successful Cisco Certification.

**Free Demo Download**

Braindump2go offers free demo for 300-208 exam (Implementing Cisco Secure Access Solutions). You can check out the interface, question quality and usability of our practice exams before you decide to buy it.

☒ Printable PDF    ☒ Premium VCE + VCE Simulator

Questions and Answers : 194 Q&As

Updated: Oct 12, 2015

~~\$429.99~~    **\$99.99**

[PDF DEMO](#)

[CHECK OUT](#)

QUESTION 111In Cisco ISE, which probe must be enabled to collect profiling data using Device Sensor? A. RADIUSB. SNMPQueryC. SNMPTrapD. Network ScanE. Syslog Answer: A QUESTION 112Which two profile attributes can be collected by a Cisco Catalyst Switch that supports Device Sensor? (Choose two.) A. LLDP agent informationB. user agentC. DHCP optionsD. open portsE. operating systemF. trunk ports Answer: AC QUESTION 113Which two profile attributes can be collected by a Cisco Wireless LAN Controller that supports Device Sensor? (Choose two.) A. LLDP agent informationB. user agentC. DHCP optionsD. open portsE. CDP agent informationF. FQDN Answer: BC QUESTION 114Which statement about Cisco ISE BYOD is true? A. Dual SSID allows EAP-TLS only when connecting to the secured SSID.B. Single SSID does not require endpoints to be registered.C. Dual SSID allows BYOD for guest users.D. Single SSID utilizes open SSID to accommodate different types of users.E. Single SSID allows PEAP-MSCHAPv2 for native supplicant provisioning. Answer: E QUESTION 115Which two types of client provisioning resources are used for BYOD implementations? (Choose two.) A. user agentB. Cisco NAC agentC. native supplicant profilesD. device sensorE. software provisioning wizards Answer: CE QUESTION 116Which protocol sends authentication and accounting in different requests? A. RADIUSB. TACACS+C. EAP-ChainingD. PEAPE. EAP-TLSAnswer: B QUESTION 117You enabled the guest session limit feature on the Cisco ISE. However, end users report that the same guest can log in from multiple devices simultaneously.Which configuration is missing on the network access device? A. RADIUS authenticationB. RADIUS accountingC. DHCP requiredD. AAA override Answer: B QUESTION 118A properly configured Cisco ISE Policy Service node is not receiving any profile data from a Cisco switch that runs Device Sensor.Which option is the most likely reason for the failure? A. Syslog is configured for the Policy Administration Node.B. RADIUS Accounting is disabled.C. The SNMP community strings are mismatched.D. RADIUS Authentication is misconfigured.E. The connected endpoints support CDP but not DHCP. Answer: B QUESTION 119Drag and Drop Question

Answer:

Drag and Drop the BYOD user experiences on an iPad on the left into the correct order on the right.

	The endpoint authenticates to secure SSID using the username and password.
	The user opens a web browser and is redirected to a registration portal.
	The endpoint installs a signed certificate that is returned from the Cisco ISE, along with the wireless network setting.
	A CoA is issued and the endpoint is reconnected to the network with the proper access.

Drag and Drop the BYOD user experiences on an iPad on the left into the correct order on the right.

	The CoA is generated on the endpoint and the user is redirected to the registration portal.
	The user opens a web browser and is redirected to a registration portal.
	The endpoint authenticates to secure SSID using the username and password.
	The endpoint installs a signed certificate that is returned from the Cisco ISE, along with the wireless network setting.
	A CoA is issued and the endpoint is reconnected to the network with the proper access.

QUESTION 120The NAC Agent v4.9.x uses which ports and protocols to communicate with an ISE Policy Service Node? A. tcp/8905, http/80, ftp/21B. tcp/8905, http/80, https/443C. udp/8905, telnet/23, https/443D. udp/8906, http/80, https/443  
Answer: B 300-208 Updated Questions are 2015 Latest Released Which 100% will Meet in Your 300-208 Test! Braindump2go New Released 300-208 Exam Dumps Contain All New Added Questions Which Will Help you Have A Totally Success in 2015 New Tear! Download our 100% Pass Guaranteed 300-208 Exam Dumps Full Version, special 10% Off Discount enjoyed!

Implementing Cisco



Questions and Answers : 194  
Q&As  
Updated: Oct 12, 2015  
~~\$129.99~~ **\$99.99**  
[PDF DEMO](#)  
[CHECK OUT](#)

**FREE DOWNLOAD: NEW UPDATED 300-208 PDF Dumps & 300-208 VCE Dumps from Braindump2go:**  
<http://www.braindump2go.com/300-208.html> (194 Q&A)