
## 2015 Latest Braindump2go 350-080 New Added Exam Questions Free Share (91-100)

CISCIO NEW UPDATED: New Updated 350-080 Exam Questions from Braindump2go 350-080 PDF Dumps and 350-080 VCE Dumps! Welcome to Download the Newest Braindump2go 350-080 VCE&PDF Dumps:

http://www.braindump2go.com/350-080.html (394 Q&As) Braindump2go New Released Cisco 350-080 Practice Tests Sample Questions Free Download! 100% Same Questions with Actual 350-080 Exam! Guaranteed 100% Pass!350-080 Dumps,350-080 Exam Dumps,350-080 Brainfump,350-080 Questions,350-080 VCE,350-080 PDF,350-080 Actual Test,350-080 Study

Guide,350-080 Book,350-080 CCIE Data Center Written Exam,350-080 Test



QUESTION 91Refer to the exhibit. Your company would like to deploy this topology design. Which statement applies? A. The configuration cannot be implemented since all fabric interconnects are members of the same VLANs, and communication will not work properly for the Backup and Mgmt networks.B. The configuration cannot be implemented because only one disjointed layer 2 network is supporteD. either Backup Net or Mgmt Net, but not both.C. The Production Network and Backup Net topologies can be implemented.D. The Production Network and Management Net topologies can be implemented.E. The topology design can be implemented fully in Cisco UCS version 2.0 or later. Answer: C QUESTION 92What interface is created when an FC Port Channel is created on a Cisco Unified Computing System? A. An interface 'san-port-channel' in NXOSB. An interface 'port-channel' in NXOSC. An interface 'port-channel' with 'mode fc' configuredD. An interface 'fc-port-channel' in NXOS Answer: A QUESTION 93Refer to the exhibit. You create a service profile within ORG C with two vNICs. Each vNIC is assigned to the MAC pool named "vmware". Which two possible MAC addresses could be assigned to the vNICs? (Choose two.) A. 00:25:B5:FF:00:01B. 00:25:B5:EE:00:01C. 00:25:B5:DD:00:01D. 00:25:B5:BB:00:01E. 00:25:B5:AA:00:01 Answer: AD QUESTION 94From the Cisco UCS CLI, how do you verify which uplink ports a blade server is using for its network connectivity? UCS-A# show pinning border-interfacesB. UCS-B# show service-profile circuitC. UCS-B(nxos)# show pinning server-interfacesD. You must statically configure which uplink the blades should use, or you will not have connectivity. Answer: C QUESTION 95Server load balancing (SLB) is the process of deciding to which server a load-balancing device should send a client request for service. Which predictors are supported on ACE in order to select the best server to fulfill a client request? (Choose three.) A. Hash address: Selects the server by using a hash value based on either the source or destination IP address, or bothB. Hash URL: Selects the server by using a hash value based on the requested URLC. Hash MAC. Selects the server by using a hash value based on either the source or destination MAC address, or bothD. Hash header: Selects the server by using a hash value based on the HTTP header nameE. Hash IP: Selects the server using a hash value based on the IP address Answer: ABD QUESTION 96Application Control Engine (ACE) can check the health of servers and server farms by configuring health probes (which are sometimes referred to as keepalives). A probe can be one of many types. Which are valid ACE probes? (Choose three.) A. HTTPB. Java scriptingC. TCL scriptingD. RADIUSE. TACACS Answer: ACD QUESTION 97When testing ICMP access to a functional load-balancing ACE VIP, it fails. What is the reason of this problem? (Choose two.) A. The interface is shut downB. An access list is denying ICMPC. Routing is not configured properlyD. vip icmp-reply is inactive Answer: BD QUESTION 98Which GSS "source access list" is used to allow access to GSS by clients when GSS is being used as the DNS? A. Client IPB. Proxy IPC. Client and proxy IPD. Neither client nor proxy IP Answer: A QUESTION 99In the event of a GSS failure in a GSS cluster, which is true? A. The current connections are rerouted via the backup GSSB. Secondary GSS cannot be used to configure the GSS clusterC. All remaining GSSs in the cluster continue responding to any new queriesD. All records in the GSS database are flushed and reconstructed again using a new master GSS Answer: C QUESTION 100A Cisco Application

Control Engine Appliance (ACE) non-admin context does not support "sticky" configuration. What is the reason for this issue? A. ACE sticky license is not installedB. ACE stickiness is not supported in a non-admin contextC. ACE stickiness resources are not defined in an admin contextD. Stickiness is configured properly in the CCIE virtual context Answer: C Braindump2go is famous for our Interactive Testing Engine that simulates a real exam environment as experienced on the actual test. We will help you become familiar with the testing environment in advance.Real 350-080 Exam Questions Plus Real 350-080 Exam Testing Environment! Braindump2go 100% Guarantees your pass of 350-080 Exam! 350-080 Dumps,394q 350-080 Exam Questions, 350-080 PDF and 350-080 VCE are also available for instant download in our website at any time! 24 hours professional assistance from IT Group! Braindump2go aims to help you pass 350-080 Exam easily!



FREE DOWNLOAD: NEW UPDATED 350-080 PDF Dumps & 350-080 VCE Dumps from Braindump2go: http://www.braindump2go.com/350-080.html (394 Q&A)