

## [2016 Mar. NEW

2016 March NEW ADDED 640-911 Exam Questions RELEASED Today!The 640-911 (DCICN) Introducing Cisco Data Center Networking exam validates a candidate's knowledge of networking concepts for the data center environment, based on Cisco NX-OS, including fundamental information on data center network function, virtualization configuration in the network, addressing schemes, and configuration skills. This is a 90 minutes (65-75 questions) Exam. 2016 NEW 640-911 Study Guides:1. Describe How a Network Works2. Configure, Verify and Troubleshoot a Switch with VLANs and Interswitch Communications Using Nexus3. Implement an IP Addressing Scheme and IP Services to Meet Network Requirements in a Medium-Size Enterprise Branch Office Network Using Nexus4.Configure, Verify, and Troubleshoot Basic Router Operation and Routing on Cisco Devices Using Nexus QUESTION 186An engineer wants to repurpose a Cisco Nexus 7010 Switch for use in a lab and needs to restore the switch to factory defaults. Which two commands are required? (Choose two.) A. write erase bootB. write erase debugC. copy running-config startup-configD. rebootE. reloadF. copy startup-config running-config Answer: AE QUESTION 187Refer to the exhibit. In which two ways does the routing table direct traffic? (Choose two.)

```
DC-Router#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       Gateway of last resort is 172.16.173.233 to network 0.0.0.0

B* 0.0.0.0/0 [20/0] via 172.16.173.233, 7w0d
   10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C   10.235.4.36/30 is directly connected, TenGigabitEthernet0/2/0
L   10.235.4.37/32 is directly connected, TenGigabitEthernet0/2/0
C   10.235.4.40/30 is directly connected, TenGigabitEthernet0/1/0
L   10.235.4.41/32 is directly connected, TenGigabitEthernet0/1/0
```

A. The router receives a default route via a dynamic routing protocol.B. 10.235.4.37 is the IP address of a local interface.C. 10.235.4.37 is the IP address of the neighbor router that is locally connected.D. 10.235.4.36 is the IP address of the directly connected neighbor.E. The gateway of last resort is statically configured. Answer: AB QUESTION 188Which option is the proper shortened representation of the IPv6 address FDFA:0000:0000:2314:00BA:AF34:0:0121? A. FDFA::2314:BA:AF34:0:121B. FDFA::2314::BA:AF34:0:0121C. FDFA::2314:BA:AF34:121D. FDFA::2314:BA:AF34::121 Answer: A QUESTION 189Which three options represent a subnet mask that allows for 60 host addresses on a subnet? (Choose three.) A. /25B. 255.255.255.192C. /26D. 255.255.255.240E. 255.255.255.248F. /28G. /30 Answer: ABC QUESTION 190A network engineer configures several VLANs using NX-OS and wants to save the changes. Which commands are used to save this configuration? A. write memoryB. copy run startC. write terminalD. copy start run Answer: B QUESTION 192A network engineer has been tasked with connecting a Nexus 5548 switch to an older Catalyst 3750. After configuring the interfaces, the engineer noticed that the end hosts did not have network connectivity and the Nexus 5548 had the following log message: %STP-2-BRIDGE\_ASSURANCE\_BLOCK: Bridge Assurance blocking port Ethernet1/27 VLAN0010 What command can solve this problem? A. configure no spanning-tree port type network on the Nexus 5548 interfaceB. configure spanning-tree mode rapid-pvstp on the Catalyst 3750C. configure switchport trunk native VLAN 10 on the Catalyst 3750 interfaceD. configure spanning-tree mode rapid-pvstp on the Nexus 5548 Answer: A QUESTION 193What two actions can be taken to enable inter-VLAN communications in the data center? (Choose two.) A. install a Layer 3 capable switch in the data centerB. deploy a router as a Layer 3 services gateway attached inside each Layer 2 VLANC. extend Layer 2 services to a Layer 3 capable VLAN using Layer 3 tunnelingD. connect Layer 2 VLANs together with 802.1Q trunksE. use a routing protocol to direct packets into the Layer 2 network Answer: AB QUESTION 195Which two statements describe two benefits of a star topology compared to a mesh topology? (Choose two.) A. New stations can be added quickly and easily.B. Troubleshooting connectivity is easier.C. There is not a single point of failure.D. A single cable failure will not bring down the entire network.E. It has the absolute least likelihood of having a collision Answer: ABQUESTION 196Unlike IPv6, which feature is available only in IPv4? A. broadcastB. anycastC. multicastD. unicast Answer: AQUESTION 197What TCP/IP layer would handle UDP traffic flows? A. internetworkB. network interfaceC. transportD. physical Answer: C QUESTION 198In which layer of the OSI model are TCP port numbers defined? A. 2B. 3C. 4D. 6E. 7 Answer: C 2016 NEW 640-911 Exam Questions Full Version 220q:  
<http://www.braindump2go.com/640-911.html>

### Compared Before Buying DCICN 640-911 PDF & VCE!

Pass4sure	Braindump2go	Test King
	100% Pass OR Money Back	
Not In Stock	220 Q&As – Real Questions	Not In Stock
/	\$99.99	/
/	Coupon Code: BDNT2014	/