

## [2017-New-ExamsBraindump2go 1Y0-240 Dumps Available for Free Downloading Today[101-110]

2017 Oct New Citrix 1Y0-240 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 1Y0-240

Questions:1.[2017 New 1Y0-240 Exam Dumps (PDF & VCE) 194Q&As Download:<https://www.braindump2go.com/1y0-240.html>

2.[2017 New 1Y0-240 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNYWRSMTFQWmNPuZQ?usp=sharing>QUESTION 101Scenario: A NetScaler engineer needs to enable access to some web servers running on an IPv6-only network. The clients connecting the services are on an IPv4 network. The engineer has already enabled IPv6 on the NetScaler. What does the engineer need to do in order to provide access to the services on the IPv6 network?A. Create an IPv6 tunnel and a IPv4 virtual server.B. Configure an IPv6 VLAN and bind the required interface.C. Create a IPv4 virtual server and bind the service group to it.D. Create an IPv6 ACL and a IPv4 virtual server and bind the ACL to the virtual server.Answer: CQUESTION 102Scenario: An engineer executes the following commands:add vlan 2bind vlan 2 -ifnum 1/2add ns ip 10.110.4.200 255.255.255.0bind vlan 2 -IPAddress 10.110.4.200 255.255.255.0What type of IP address has been added to the NetScaler?A. VIP addressB. NSIP addressC. SNIP addressD. GSLB Site IP addressAnswer: CQUESTION 103Scenario: A network engineer needs to configure Citrix NetScaler to provide Access Gateway services to VLAN 2 using interface 1/1 only, while also using interface 1/2 to provide load balancing services to VLAN 3. How could this result be achieved?A. Disable static route advertisement.B. Disable layer 2 modeCreate 2 untagged VLANs - VLAN 2 and VLAN 3Bind VLAN 2 to Interface 1/1Bind VLAN 3 to Interface 1/2C. Enable Layer 3 modeCreate a Channel Interface using Interface 1/1 and 1/2 Create 2 VMACsBind a VMAC to interface 1/1 and 1/2D. Configure policy-based routing using the Interface option as a filter.Answer: BQUESTION 104Scenario: A network engineer needs to re-configure the NetScaler to utilize two new VLANs - VLAN2 and VLAN3. VLAN2 is an untagged VLAN and VLAN3 will require a .1q compliant tag. Interface 1/1 is the only interface that will be used on the NetScaler. How could the engineer configure the NetScaler so that it can communicate with both networks?A. Change the NSVLAN to 3Add VLAN 2 and bind interface 1/1 as untaggedB. Enable the Tag all VLANs option on interface 1/1.C. Add VLAN2 and bind interface 1/1 as untaggedAdd VLAN3 and bind interface 1/1 as taggedD. Add a SNIP for each VLANEnable management access on the SNIP for VLAN3Answer: CQUESTION 105Why would an engineer want to specify a TCP Profile for a specific service group?A. To enable use of features like SSL over TCP for that specific service group.B. To adjust the TCP settings for traffic to and from that specific service group.C. To use a specific SNIP for traffic to the back-end servers in that service group.D. To enable features like use source IP, TCP keep alive and TCP buffering for a specific service group.Answer: BQUESTION 106Scenario: The NetScaler is connected to two subnets. The NSIP is 10.2.9.12. The external SNIP is 10.2.7.3. The MIP for internal access is 10.2.9.3. Web servers, authentication servers and time servers are on the 10.2.10.0/24 network which is available through the 10.2.9.1 router. The external firewall has the 10.2.7.1 address. Traffic bound for Internet clients should flow through the external firewall. Which command should be used to set the default route?A. add route 0.0.0.0 0.0.0.0 10.2.7.1B. add route 0.0.0.0 0.0.0.0 10.2.9.1C. add route 10.0.0.0 255.0.0.0 10.2.9.1D. add route 10.0.0.0 255.0.0.0 10.2.7.1Answer: AQUESTION 107Some SSL certificate files may be missing from a NetScaler appliance. Which directory should an engineer check to determine which files are missing?A. /nsconfig/sslB. /nsconfig/sshC. flash/nsconfig/D. /var/netscaler/ssl/Answer: AQUESTION 108Scenario: A call center has deployed Access Gateway Enterprise to provide its employees with access to work resources from home. Due to the number of available licenses, only selected employees should access the environment remotely based on their user account information. How could the engineer configure access to meet the needs of this scenario?A. Configure a Pre-authentication Policy.B. Configure an Authentication Server using a search filter.C. Configure an Authentication Policy using Client based expressions.D. Add the selected employee accounts to the Local Authentication policy.Answer: BQUESTION 109How could an engineer configure a monitor to ensure that a server is marked as DOWN if the monitor test is successful?A. Enable the LRTM option for the monitorB. Enable the Reverse option for the monitorC. Disable Down state flush for the service groupD. Disable the Health monitoring option for the service groupAnswer: BQUESTION 110A network engineer should use a HTTP-ECV monitor type to control the status of a load balanced web server resource when \_\_\_\_\_. (Choose the correct option to complete the sentence.)A. checking for multiple HTTP response codesB. wanting to use a customized HTTP RequestC. checking for a specific pattern in the HTTP Response bodyD. checking for a specific pattern in the HTTP Response headerAnswer: C!!!RECOMMEND!!!1.[2017 New 1Y0-240 Exam Dumps (PDF & VCE) 194Q&As Download:<https://www.braindump2go.com/1y0-240.html>2.[2017 New 1Y0-240 Study Guide Video: YouTube Video: [YouTube.com/watch?v=IooNx0GMaHQ](https://www.youtube.com/watch?v=IooNx0GMaHQ)