[2018-Apr.-New100% Real 300-101 PDF and VCE Exam Dumps 557Q-Braindump2go[523-535

2018 April New Cisco 300-101 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 300-101 Real Exam Questions:1.|2018 Latest 300-101 Exam Dumps (PDF & VCE) 557Q&As Download:https://www.braindump2go.com/300-101.html 2.|2018 Latest 300-101 Exam Questions & Answers Download: **https://drive.google.com/drive/folders/0B75b5xYLjSSNeXNhZVlPaDA3dDA?usp=sharing**QUESTION 523Refer to the Exhibit. A network engineer has configured NTP on a Cisco router, but the time on the router is still incorrect. What is the reason for this problem?




www.Braindump2go.com

A. The router is not syncing with the peer, even though the NTP request and response packets are being exchanged.B. The router is not syncing with peer, and the NTP request and response packets are not being exchanged.C. The router is syncing with the peer, and the NTP request and response packets are being exchanged.D. The router is dropping all NTP packets.**Answer: D** QUESTION 524Which technology uses the many-to-one method of mapping IP addresses?A. static NATB. dynamic NATC. NAT-PTD. PATAnswer: DExplanation:Overloading--Maps multiple unregistered IP addresses to a single registered IP address (many to one) using different ports. This method is also known as Port Address Translation (PAT). By using overloading, thousands of users can be connected to the Internet by using only one real global IP addressQUESTION 525Which version MPLS?A. all versions of NetFlowB. NetFlow version 9C. NetFlow version 8D. NetFlow version 5E. NetFlow version 8 and 9**Answer: B** QUESTION 526What are two limitations when in use of NPTv6 for IPV6 vs IPV6 Address translation?A. stateful address translationB. a limit of 32 1-to-1 translationsC. lack of overloading functionalityD. identify all interfaces NAT inside or outsideE. 1-to-1 prefix rewriteF. mismatched prefix allocations**Answer: CE**QUESTION 527Which two statements about NTP stratum are true? (Choose two)A. Stratum 15 indicates a device that is not synchronizedB. Stratum 1 devices receive their time from a peer that is connected directly to an authoritative time source.C. The highest stratum level a synchronized device can have is 16.D. Stratum 2 devices receive their time from a peer that is connected directly to an authoritative time sourceE. Stratum 0 devices are connected directly to an authoritative time sourceF. Stratum 1 devices are connected directly to an authoritative time source**Answer: BF**QUESTION 528What is the result of the command ip flow-export destination 10.10.10.1 5858?A. It configures the router to export cache flow information to IP 10.10.10.1 on port UDP/5858.B. It configures the router to export cache flow information about flows with destination IP 10.10.10.1 and port UDP/5858.C. It configures the router to receive cache flow information from IP 10.10.10.1 on port UDP/5858.D. It configures the router to receive cache flow information about flows with destination IP 10.10.10.1 and port UDP/5858.**Answer: A**QUESTION 529Which two options can you use to configure an EIGRP stub router? (Choose two)A. summary-onlyB. receive-onlyC. externalD. summaryE. totally-stubbyF. not-so-stubbyAnswer: BDExplanation:
https://www.cisco.com/en/US/technologies/tk648/tk365/technologies_white_paper0900aec d8023df6f.htmleigrp stub [[receive-only] || [connected] [static] [summary] [redistributed]] The following options are available:?Receive-only: router only accepts, but does not explicitly advertise, any routes. This option may not be used in combination with any other options. ?Connected: router advertises directly-connected networks ?Static: router advertises any configured static routes ?Summary: router advertises any configured summarized routes ?Redistributed: router advertises any routes learned from another protocol, such as OSPF The eigrp stub configuration need only be entered on the spoke routers. The hub routers determine that they are talking to a stub router by examining the TLV in the HELLO packet.QUESTION 530Which technology is required on an EVN trunk


interface?A. 802.1qB. NATC. VRF-LiteD. IS-IS**Answer: C**QUESTION 531Refer to Exhibit. A network engineer is unable to make VRF lite EIGRP adjacency work. There is nothing wrong with communication between R1 and R2. What command will eliminate the issue when executed on both routers?



A. (config-router-af)#autonomous-system 100B. (config)#ip-multicast-routingC. (config-vrf)#route-target both 100:1D. config-router-af)#network 209.165.202.128.0.0.0.31**Answer: A**QUESTION 532Refer to the exhibit. You have correctly identified the inside and outside interfaces in the NAT configuration of this device. Which effect of this configuration is true?



A. dynamic NATB. static NATC. PATD. NAT64**Answer: C**QUESTION 533Which condition can cause unicast reverse path forwarding to fail?A. split horizonB. STP convergenceC. PortFast security violationD. asymmetric routing**Answer: D** QUESTION 534Refer to the following:Logging Console7Which option is one of the effects entering this command on a Cisco IOS router, with no additional logging configuration?A. Debug messages can be seen on the console by enabling "terminal monitor."B. Debug messages are logged only on active console connections.C. A user that is connected via SSH sees level 7 messagesD. The router can experience high CPU utilization**Answer: D**QUESTION 535Refer to exhibit. A user calls from another branch office with a request to establish a simple VPN tunel to test a new router's tunneling capability.Based on the configuration in the exhibit, which type of tunnel was configured?



]A. PPTPB. IPsec site-to-siteC. 6to4D. EZVPN**Answer: B**RECOMMEND!!!1.|2018 Latest 300-101 Exam Dumps (PDF & VCE) 557Q&As Download:https://www.braindump2go.com/300-101.html 2.|2018 Latest 300-101 Study Guide Video: YouTube Video: YouTube.com/watch?v=5_NSbPNcqms