

## [2018-April-New100% Success-Braindump2go 300-180 Dumps PDF 374Q Instant Download][124-134

2018 April New Cisco 300-180 Exam Dumps with PDF and VCE Free Updated Today! Following are some new CV0-001 Real

Exam Questions:1.[2018 Latest 300-180 Exam Dumps (PDF & VCE) 374Q&As Download:

<https://www.braindump2go.com/300-180.html>2.[2018 Latest 300-180 Exam Questions & Answers Download:

<https://drive.google.com/drive/folders/0B75b5xYLjSSNRfptN0xiTENBMzA?usp=sharing>  
**QUESTION 124**Which option is the cause when a DIMM is marked as bad?  
A. More than 16000 errors were witnessed during test execution during BIOS.  
B. DIMM Blacklisting is enabled.  
C. The DIMM is missing.  
D. The bank of DIMMs is composed of different size DIMMs.  
**Answer: A**  
**QUESTION 125**As an experienced technician, you are responsible for Technical Support in your company. A user calls to ask you with which Cisco UCS feature he could send specific functional data using call home. How will you reply?  
A. call home profiles  
B. call home alert groups  
C. call home port groups  
D. call home threshold groups  
**Answer: B**  
**QUESTION 126**As an experienced technician, you should be familiar with components of the UCS solution. Which of the following have beacon LEDs? (Choose two)  
A. fabric interconnect  
B. monitors  
C. blades  
D. chassis  
**Answer: CD**  
**QUESTION 127**Refer to the following statements, which one about full-state backup is the most accurate?  
A. used for either a single or dual UCS catastrophic failure  
B. stored as gzipped tarball  
C. can be restored with no special requirements  
D. easy to modify as needed  
**Answer: A**  
**QUESTION 128**Which two of the following descriptions best describe opt-in models? (Choose two)  
A. A logical server opt-in model uses hardware values as identifiers  
B. A basic opt-in model uses hardware values as identifiers  
C. A logical server opt-in model uses virtualized identifiers  
D. A basic opt-in model uses virtualized identifiers  
**Answer: BC**  
**QUESTION 129**Refer to the following items, which is contained in a user object of the UCS system contain? (Choose two)  
A. Microsoft Active Directory credentials  
B. Authentication and Authorization credentials  
C. LDAP assignment  
D. Role assignment  
**Answer: CD**  
**QUESTION 130**Which of the following statements correctly describes the high availability in the Cisco UCS?  
A. Each group is identified by a floating node ID  
B. A node is one of the two(2) Fabric Interconnects  
C. A node is one of the two(2) CMCs  
D. A group is a set of four(4) nodes  
**Answer: B**  
**QUESTION 131**On a Cisco Nexus 5000 Series Switch, which two options are valid traffic sources that can be monitored, when configuring a SPAN session for a port channel?  
A. egress and the SAN port channel only  
B. ingress and the SAN port channel only  
C. ingress and egress only  
D. ingress, egress, and the SAN port channel  
**Answer: B**  
**QUESTION 132**You attempt to boot a supported Linux operating system live image from the eUSB in a Cisco UCS blade-server environment, but the boot fails. Which option is the most likely cause of the failure?  
A. In the Service Profile, a device other than the eUSB is set first in the boot order for the server.  
B. The eUSB license is unavailable or the grace period of the license is expired.  
C. The blade servers are unable to boot from the eUSB. The eUSB is used only for virtual machines.  
D. Access to the eUSB is disabled for that blade server by Power Manager.  
**Answer: A**  
**QUESTION 133**Hotspot QuestionWhy is Virtual Fibre Channel interface 19 in err-disable state?  
A. Missing transceiver  
B. Virtual interface is not bound to a physical interface  
C. The associated physical interface is down  
D. VSAN to VLAN binding mis-configured  
**Answer: D**  
**QUESTION 134**Hotspot QuestionRefer to Exhibit 2. Which of the following options is true about why this C-Series vHBA will not allow SAN boot?  
A. The WWPN and WWNN must match  
B. Persistent Binding is required by all operating systems  
C. The default VLAN must match the FCoE VLAN  
D. The Class of Service must be set to '1' to negotiate Priority Flow Control for FCoE traffic  
**Answer: A**  
**!!!RECOMMEND!!!**1.[2018 Latest 300-180 Exam Dumps (PDF & VCE) 374Q&As Download:<https://www.braindump2go.com/300-180.html>2.[2018 Latest 300-180 Study Guide Video: YouTube Video: [YouTube.com/watch?v=CAOPD5fGrmc](https://www.youtube.com/watch?v=CAOPD5fGrmc)