

## PDF & VCE Format 642-035 Dumps With New Updated Exam Questions and Answers Free Download From Braindump2go (83-93)

**CISCO OFFICIAL: 642-035 Exam Questions has been Updated Today! Free Download the Latest 642-035 Dumps PDF and 642-035 Exam VCE Now!** New Released Braindump2go Cisco 642-035 Dumps PDF - Questions and Answers Updated with Cisco Official Exam Center! Visit Braindump2go and download our 642-035 Exam Questions Now, Pass 642-035 100% at your first time! Vendor: CiscoExam Code: 642-035Exam Name: PRO: Troubleshooting Cisco Unified Computing (DCUCT)Keywords: 642-035 Exam Dumps,642-035 Practice Tests,642-035 Practice Exams,642-035 Exam Questions,642-035 PDF,642-035 VCE Free,642-035 Book,642-035 E-Book,642-035 Study Guide,642-035 Braindump,642-035 Prep Guide

### Compared Before Buying Cisco 642-035 PDF

Pass4sure	Braindump2go	
	100% Pass OR Money Back	
Not In Stock	130 Q&As – Real Questions	N
/	\$99.99	/
/	Coupon Code: BDNT2014	/

Cisco 642-035 Dumps VCE&PDF Download: <http://www.braindump2go.com/642-035.html> QUESTION 83Refer to exhibit. A Cisco UCS admin is troubleshooting an issue with a vNIC not coming up on a blade. When looking at the CLI of the "Fabric Interconnect",the admin runs this command to view the status of the interface. Which option describes a possible reason why the interface is stuck in an "initializing" state?

```
aci-sol-calo-ucsb-A(nxos)# show interface vethernet 813
Vethernet813 is down (initializing)
  Bound Interface is port-channel1282
  Port description is server 1/1, vNIC Data-A
  Hardware is Virtual, address is 8c60.4f01.4420
  Port mode is trunk
  Speed is auto-speed
  Duplex mode is auto
  300 seconds input rate 0 bits/sec 0 packets/sec
  300 seconds output rate 0 bits/sec 0 packets/sec
  Rx
    0 unicast packets 0 multicast packets 115 broadcast packets
    115 input packets 32934 bytes
    0 input packet drops
  Tx
    0 unicast packets 29 multicast packets 0 broadcast packets
    29 output packets 8729 bytes
    0 flood packets
    0 output packet drops
```

A. The service profile is not applied to a blade.B. The VLANs defined on the vNIC are not defined on a matching uplink port.  
C. The uplink port is down.D. The QoS policy on the vNIC is invalid.E. The MTU on the vNIC is higher than the MTU configured in the QoS system class. Answer: C QUESTION 84Which two options are causes for failure of a Cisco C-Series server that is configured to boot from SAN? (Choose two.) A. The boot LUN ID is not 0.B. The iSCSI target is only available via one via one path through the network.C. C-Series does not support boot from SAN.D. The KVM dongle is attached to the front of the server with a USB stick installed.E. Under the FCoE properties on the vNIC adapter, the FCoE VLAN ID is set to 10.F. The boot table for fc0 has not been configured. Answer: DF QUESTION 85Which command on the Fabric Interconnect displays packet statistics for a given QoS group and MTU size? A. show policy-map interface ethernet x/yB. show queuing interface ethernet x/y  
C. show interface ethernet x/yD. show class-map type qosE. show interface queuing ethernet x/y Answer: B QUESTION 86A Cisco UCS admin is trying to integrate Cisco UCS Manager with Active Directory Authentication. After the configuration is done, the admin is still unable to log in using LDAP credentials. When running a debug on the Fabric Interconnect, this error is displayed: ldap\_build\_roles\_and\_locales\_from\_attr: No attr for usr profileWhich step was missed in the configuration? A. The LDAP provider was not configured correctly.B. The proper RBAC role(s) were not assigned to the user.C. Cisco UCS Manager 2.1 is required for LDAP integration.D. The "Attribute" field in Cisco UCS was left blank. Answer: B QUESTION 87Which three requirements are needed to configure a blade to boot successfully from Fibre Channel? (Choose three.) A. zoningB. LUN maskingC. WWPN device aliasD. boot from SAN policyE. SAN connectivity policyF. port assignmentG. target WWPN needs to be set in the boot from SAN policy Answer: ABD QUESTION 88Which description of a core file is true? A. It is generated by a system failure.B. It is generated by a process failure.C. It is generated by a component failure.D. It is generated by a hardware failure. Answer: B QUESTION 89Which logs are used to troubleshoot hardware failure? A. system event logB. audit logC. accounting logD. gateway logsE. system log Answer: A QUESTION 90A UCS Admin is trying to launch the

KVM console but it is failing to launch. All IP Pools for mgmt are configured and the CIMC has an address in UCSM. They SSH to the fabric Interconnect and run an ethanalyzer while issuing a ping from their local PC to the KVM IP address. The ping is successful but they do not see the ICMP requests and replies displayed in the capture. Here is the filter they used:FIA(nxos)# ethanalyzer local interface mgmt display-filter icmp limit-captured-frames 0What could be the reason pings are not seen in the capture and the KVM is failing to load? A. Java settings are preventing the KVM from loadingB. There is a duplicate IP address for that CIMC addressC. The switch upstream from the FI has the wrong vlan configuredD. The CIMC IP pool is in the same subnet as the Fabric Interconnects mgmt 0 interface Answer: B QUESTION 91Where do you configure users so that they cannot access resources that belong to other organizations? A. rolesB. domain separationC. localsD. VDCs Answer: C QUESTION 92What is the correct procedure to change Ethernet switching modes? A. Navigate to the subordinate Fabric Interconnect in the GUI, choose "Set Ethernet Switching mode", wait for it to come back up, and repeat on the primary FI.B. Navigate to either Fabric Interconnect in the GUI, choose "Set Ethernet Switching mode", and wait while both FIs reboot simultaneously.C. Navigate to either Fabric Interconnect in the GUI and transparently update the mode to switching. Repeat on the other Fabric Interconnect.D. Simply start using the switching features. The Fabric Interconnect automatically reconfigures to use Ethernet Switching Mode. Answer: B QUESTION 93Which power policy should be chosen to maximize the performance of a Cisco UCS system with four PSUs and eight blades? A. non-redundantB. N+1C. gridD. performance Answer: C Braindump2go Latest 642-035 Exam Dumps Released! 100% Real Questions - Dumps Qulification is the secret of Success! Prepare yourself to Face the 642-035 Exam with Real Exam Questions from Cisco Official Exam Center, walk into the Testing Centre with confidence.

Compared Before Buying C	
Pass4sure	Bra
	100% P
Not In Stock	130 Q&As
/	\$99.99
/	Coupon C

<http://www.braindump2go.com/642-035.html>