This page was exported from - Braindump2go Exam Dumps Free Download
Export date: Thu Mar 28 21:21:43 2024 / +0000 GMT

[Feb-2019100% Real Exam Questions-Braindump2go 200-125 VCE and PDF 1129Q Download(Q286-Q296)

2019/February Braindump2go 200-125 Exam Dumps with PDF and VCE New Updated Today! Following are some new 200-125 Real Exam Questions:]1.|2019 Latest 200-125 Exam Dumps (PDF & VCE) 1129Q&As Instant Download:https://www.braindump2go.com/200-125.html**2.|2019 Latest 200-125 Exam Questions & Answers Instant Download: https://drive.google.com/drive/folders/0B75b5xYLjSSNanR4T1lPU1l5cmM?usp=sharing**QUESTION 286What are three factors a network administrator must consider before implementing Netflow in the network? (Choose three.)A. CPU utilizationB. where Netflow data will be sentC. number of devices exporting Netflow dataD. port availabilityE. SNMP versionF. WAN encapsulation**Answer: ABC**QUESTION 287Which two statements about the OSPF Router ID are true? (Choose two.)A. It identifies the source of a Type 1 LSA.B. It should be the same on all routers in an OSPF routing instance.C. By default, the lowest IP address on the router becomes the OSPF Router ID.D. The router automatically chooses the IP address of a loopback as the OSPF Router ID.E. It is created using the MAC Address of the loopback interface.**Answer: AD**QUESTION 288What parameter can be different on ports within an EtherChannel?A. speedB. DTP negotiation settingsC. trunk encapsulationD. duplex**Answer: B**QUESTION 289What are two benefits of using a single OSPF area network design? (Choose two.)A. It is less CPU intensive for routers in the single area.B. It reduces the types of LSAs that are generated.C. It removes the need for virtual links.D. It increases LSA response times.E. It reduces the number of required OSPF neighbor adjacencies.**Answer: BC** QUESTION 290Refer to the exhibit. What set of commands was configured on interface Fa0/3 to produce the given output?A. interface FastEthernet 0/3channel-group 1 mode desirableswitchport trunk encapsulation dot1qswitchport mode trunkB. interface FastEthernet 0/3channel-group 2 mode passiveswitchport trunk encapsulation dot1qswitchport mode trunkC. interface FastEthernet 0/3channel-group 2 mode activeswitchport trunk encapsulation dot1qswitchport mode trunkD. interface FastEthernet 0/3channel-group 2 mode onswitchport trunk encapsulation dot1qswitchport mode trunk**Answer: B**QUESTION 291Refer to the exhibit. If the devices produced the given output, what is the cause of the EtherChannel problem?A. SW1's Fa0/1 interface is administratively shut down.B. There is an encapsulation mismatch between SW1's Fa0/1 and SW2's Fa0/1 interfaces.C. There is an MTU mismatch between SW1's Fa0/1 and SW2's Fa0/1 interfaces.D. There is a speed mismatch between SW1's Fa0/1 and SW2's Fa0/1 interfaces.**Answer: D**QUESTION 292What are two enhancements that OSPFv3 supports over OSPFv2? (Choose two.)A. It requires the use of ARP.B. It can support multiple IPv6 subnets on a single link.C. It supports up to 2 instances of OSPFv3 over a common link.D. It routes over links rather than over networks.**Answer: BD**QUESTION 293When a router undergoes the exchange protocol within OSPF, in what order does it pass through each state?A. exstart state > loading state > exchange state > full stateB. exstart state > exchange state > loading state > full stateC. exstart state > full state > loading state > exchange stateD. loading state > exchange state > full state > exstart state**Answer: B**QUESTION 294A network administrator creates a layer 3 EtherChannel, bundling four interfaces into channel group 1. On what interface is the IP address configured?A. the port-channel 1 interfaceB. the highest number member interfaceC. all member interfacesD. the lowest number member interface**Answer: A**QUESTION 295Refer to the exhibit. If the router Cisco returns the given output and has not had its router ID set manually, what value will OSPF use as its router ID?A. 192.168.1.1B. 172.16.1.1C. 1.1.1.1D. 2.2.2.2**Answer: D**QUESTION 296What command sequence will configure a router to run OSPF and add network 10.1.1.0 /24 to area 0?A. router ospf area 0 network 10.1.1.0 255.255.255.0 area 0B. router ospfnetwork 10.1.1.0 0.0.0.255C. router ospf 1network 10.1.1.0 0.0.0.255 area 0 D. router ospf area 0network 10.1.1.0 0.0.0.255 area 0E. router ospfnetwork 10.1.1.0 255.255.255.0 area 0F. router ospf 1 network 10.1.1.0 0.0.0.255**Answer: C**!!!RECOMMEND!!!1.|2019 Latest 200-125 Exam Dumps (PDF & VCE) 1129Q&As Instant Download:https://www.braindump2go.com/200-125.html**2.|2019 Latest 200-125 Study Guide Video:** YouTube Video: YouTube.com/watch?v=rpmyHF5Fank